



Model 1



Model 2



Model 3



Model 4

Fork in stainless designed for optimum kneading quality in all type of doughs. Bowl is made of stainless steel and dough capacity changes according to desired volume.
Available capacity 20 kg flour (26 Lt) up to 400 kg flour (685 Lt)
Easy maintenance, cleaning and use.

- One Speed : 45 rpm (standard))
- Monophase 220 V or Triphase 380 V 50 Hz
- Bowl Break
- Body and table HRU 3237 Sheetmetal
- Low tension 24 Volt
- One Speed : 45 rpm
- Structure in epoxy powdered
- Safety grid
- Low tension 24 Volt

Optional

- 2 Speeds with 2 timers : 45 rpm – 72 rpm
- Stainless Steel body



**Double Speed
2 Timers**



Health and safety

- The basic health and safety requirements of Machinery Directive
- The basic requirements of Electromagnetic Compatibility Directive

MODEL				FRKM 010R	FRKM 020R	FRKM 25R	FRKM 020D	FRKM 025D	FRKM 040D	FRKM 050D	FRKM 060D	FRKM 100D	FRKM 150D	FRKM 200D	FRKM 250D	FRKM 400D
Capacity	Capacité	Kapazität	Lt	26	34	55	34	55		120	145	210	300	400	500	650
Capacity Flour	Capacité Farine	Kapazität Mehl	Kg	10	20	25	20	25	40	50	60	100	150	200	250	400
Capacity Dough	Capacité Pate	Kapazität Teig	Kg	15	30	40	30	40	60	75	90	150	225	300	375	600
Bowl	Cuvé	Kessel	Ø X h (mm)	430X215	500X250	600X300	500X250	600X300	700X350	750X275	800X400	900X450	1000X500	1100X550	1200X600	1300X650
Width	Largeur	Breite	mm	550	660	720	710	780	880	920	1020	1080	1120	1200	1370	1400
Depth	Longueur	Länge	mm	760	900	970	1070	1230	1350	1160	1540	1580	1640	1790	2110	2320
Height	Hauteur	Höhe	mm	730	765	790	810	830	950	955	985	1080	1180	1240	1320	1400
Weight	Poids	Nettogewicht	Kg	80	100	106	154	165	230	197	252	324	425	446	525	620
Power	Puissance électrique	Motorleistung	kW	0,55	0,55	0,75	0,55	0,75	1,1	1,5	1,5	2,5	3	4	5,5	6,5
				Reducer Type				Differential Type								

Example photo is double speed with stainless steel body. Tugkan has the right to change dimensions and model without any notice



Rami, Yenimahalle, Hidirbey Cd. 34055
Eyup Istanbul Turkey
Tel / Fax : +90 212 616 83 28
www.serokan.com order@serokan.com